

| HARDWARE FEATURES | |
|--------------------------|--|
| Standards and Protocols | IEEE 802.3i/802.3u/ 802.3ab/802.3x |
| Interface | 5× 10/100/1000Mbps, Auto-Negotiation, Auto-MDI/MDIX Ports |
| Fan Quantity | Fanless |
| External Power Supply | External Power Adapter (Output: 5VDC/0.6A) |
| Dimensions (W x D x H) | 3.5 × 2.8 × 0.9 in. (90 × 72 × 23 mm) |
| Max Power Consumption | 3.7W |
| Max Heat Dissipation | 12.6 BTU/h |
| PERFORMANCE | |
| Switching Capacity | 10 Gbps |
| Packet Forwarding Rate | 7.4 Mpps |
| MAC Address Table | 2K |
| Packet Buffer Memory | 1.5 Mb |
| Jumbo Frame | 16 KB |
| SOFTWARE FEATURES | |
| Advanced Features | Green Technology 802.3X Flow Control Back Pressure |
| Transfer Method | Store and Forward |
| OTHERS | |
| Certification | FCC, RoHS |
| Package Contents | 5-Port 10/100/1000Mbps Desktop Switch Power Adapter Installation Guide |
| Environment | Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~60°C (-40°F~140°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing |